





ACCESSORI ACCESSORIES

	Codice Code	Finitura Finishing	Dimensioni Dimensions	Descrizione Description
	20305-B 20305-GR	bianco white grigio grey		Kit fissaggio e alimentazione Kit di fissaggio installabile a parete o soffitto, composto da scatola di alimentazione, cavo e agganci. Lunghezza massima del cavo in dotazione (cavo a un conduttore) 1000mm. Fastening and power supply kit Wall or ceiling fastening kit, with power supply box, cable and hooks. Maximum length of supplied cable (cable with one wire) 1000mm.
	WIR501	cromo chrome		Sostegno tesata e distanziatore Distanziatore in ottone cromato, per tendere i cavi da parete a soffitto o da soffitto a soffitto, altezza 200mm. Accessorio utilizzabile anche come sostegno. Cable support and ceiling spacer Spacer in chrome brass, to stretch the cables from wall to ceiling or from ceiling to ceiling, 200mm height. It can also be used as a support.
	20315			Kit fissaggio Kit di fissaggio installabile a parete o soffitto con ganci (4 pezzi). Fastening kit Wall or ceiling fastening kit with hooks (4 pieces).
	20310			Kit sostegno Kit di sostegno per eliminare la flessione dei cavi in installazioni lunghe o con diversi apparecchi. Composto da fune in acciaio, agganci a soffitto e agganci di ancoraggio alla tesata. Lunghezza massima della fune in dotazione 1500mm. Support kit Support kit to prevent cable bending in long installations or with different luminaires, consisting of steel cable, ceiling hooks and cable fastening hooks. Maximum length of the supplied cable 1500mm.
	20320-B 20320-GR	bianco white grigio grey		Kit connettori Kit connettori per alimentare più linee, composto da cavo a un conduttore e coppia di connettori con ruba corrente. Fastening kit Wire system supply connector kit allowing conductor coupling comprising cable and clamp on connector blocks
	C.73-15 (15 mt) C.73-30 (30 mt) C.73-50 (50 mt) C.73-100 (100 mt)			Cavo per doppia accensione Cavo elettrico conduttore 2x1,5mm ² e cavo d'acciaio di tenuta. Disponibile in matassa da 15, 30, 50 e 100 metri. Cable for double switching Supply cable 2x1,5mm ² with steel suspension wire. Available in 15, 30, 50 and 100 meters length.
	C.74-15 (15 mt) C.74-30 (30 mt) C.74-50 (50 mt) C.74-100 (100 mt)			Cavo per singola accensione Cavo elettrico conduttore 1x1,5mm ² e cavo d'acciaio di tenuta. Disponibile in matassa da 15, 30, 50 e 100 metri. Cable for single switching Supply cable 1x1,5mm ² with steel suspension wire. Available in 15, 30, 50 and 100 meters length.