

LED A++ IP54 CE

Codice Code	Finitura Finishing	K	Flusso Flux	CRI	Potenza Wattage	Dimensioni Dimension	Ottica Optics	Peso Weight
KUB001B	bianco white	3000K	1530 lm	≥ 80	20W - 220/240V	Ø90x105 mm		0,7 Kg
KUB002B	bianco white	4000K	1620 lm	≥ 80	20W - 220/240V	Ø90x105 mm		0,7 Kg
KUB001GR	grigio grey	3000K	1530 lm	≥ 80	20W - 220/240V	Ø90x105 mm		0,7 Kg
KUB002GR	grigio grey	4000K	1620 lm	≥ 80	20W - 220/240V	Ø90x105 mm		0,7 Kg
KUB001AN	antracite anthracite	3000K	1530 lm	≥ 80	20W - 220/240V	Ø90x105 mm		0,7 Kg
KUB002AN	antracite anthracite	4000K	1620 lm	≥ 80	20W - 220/240V	Ø90x105 mm		0,7 Kg



E-A++ IP54 CE

Codice Code	Finitura Finishing	Base	Flusso Flux	CRI	Potenza Wattage	Dimensioni Dimension	Ottica Optics	Peso Weight
KUB005B	bianco white	GU10	—	—	1x20W LED max-220V	Ø90x105 mm	—	0,6 Kg
KUB005GR	grigio grey	GU10	—	—	1x20W LED max-220V	Ø90x105 mm	—	0,6 Kg
KUB005AN	antracite anthracite	GU10	—	—	1x20W LED max-220V	Ø90x105 mm	—	0,6 Kg

