


LED A++ IP54 CE

Codice Code	Finitura Finishing	K	Flusso Flux	CRI	Potenza Wattage	Dimensioni Dimension	Ottica Optics	Peso Weight
KUB003B	bianco white	3000K	1610 lm	≥ 80	20W - 220/240V	95x95x105 mm		0,9 Kg
KUB004B	bianco white	4000K	1700 lm	≥ 80	20W - 220/240V	95x95x105 mm		0,9 Kg
KUB003GR	grigio grey	3000K	1610 lm	≥ 80	20W - 220/240V	95x95x105 mm		0,9 Kg
KUB004GR	grigio grey	4000K	1700 lm	≥ 80	20W - 220/240V	95x95x105 mm		0,9 Kg
KUB003AN	antracite anthracite	3000K	1610 lm	≥ 80	20W - 220/240V	95x95x105 mm		0,9 Kg
KUB004AN	antracite anthracite	4000K	1700 lm	≥ 80	20W - 220/240V	95x95x105 mm		0,9 Kg



E-A++ IP54 CE

Codice Code	Finitura Finishing		Flusso Flux	CRI	Potenza Wattage	Dimensioni Dimension	Ottica Optics	Peso Weight
KUB006B	bianco white	GU10	—	—	1x20 W LED max-220V	95x95x105 mm	—	0,8 Kg
KUB006GR	grigio grey	GU10	—	—	1x20 W LED max-220V	95x95x105 mm	—	0,8 Kg
KUB006AN	antracite anthracite	GU10	—	—	1x20 W LED max-220V	95x95x105 mm	—	0,8 Kg

