


Codice Code	Finitura Finishing	K	Flusso Flux	CRI	Potenza Wattage	Dimensioni Dimension	Ottica Optics	Peso Weight
10014-GR-LED-S	grigio grey	3000K	1350 lm	≥ 80	15W - 220/240V	Ø275x86 mm		2,5 Kg
OBO001GR	grigio grey	4000K	1430 lm	≥ 80	15W - 220/240V	Ø275x86 mm		2,5 Kg
10014-AN-LED-S	antracite anthracite	3000K	1350 lm	≥ 80	15W - 220/240V	Ø275x86 mm		2,5 Kg
OBO001AN	antracite anthracite	4000K	1430 lm	≥ 80	15W - 220/240V	Ø275x86 mm		2,5 Kg
10014-MA-LED-S	marrone brown	3000K	1350 lm	≥ 80	15W - 220/240V	Ø275x86 mm		2,5 Kg
OBO001MA	marrone brown	4000K	1430 lm	≥ 80	15W - 220/240V	Ø275x86 mm		2,5 Kg



Informazioni sensore Sensor information




Altezza installazione
Height of installation

2,5-3,5 m



MIN: 1m
Max: 8m

Campo di regolazione
distanza di rilevamento
Sensing distance adjustment range



360°

Campo di regolazione angolo
di rilevamento
Sensing angle adjustment range

SENS TIME LUX



Potenza di trasmissione < 0,2 mW
Transmission power < 0,2 mW

Codice Code	Finitura Finishing		Flusso Flux	CRI	Potenza Wattage	Dimensioni Dimension	Ottica Optics	Peso Weight
10014-GR	grigio grey	E27	—	—	2x75W max - 220V	Ø275x86 mm	—	2,5 Kg
10014-AN	antracite anthracite	E27	—	—	2x75W max - 220V	Ø275x86 mm	—	2,5 Kg
10014-MA	marrone brown	E27	—	—	2x75W max - 220V	Ø275x86 mm	—	2,5 Kg

